

Client Name



Post-Installation Tasks (11.5.5) - ORACLESID Instance				
Task	Date	Status	DBA	Notes
Rename Installer Location File				mv /var/opt/oracle/oraInst.loc to /var/opt/oracle/ORACLESIDoraInst.loc
Delete Temporary Installation Files				rm /tmp/* and rm /var/tmp/* - Owned by ORACLESID UNIX Account
Rename Installation Log File				mv \$APPL_BASE/ORACLESIDinst/DATE.log to \$APPL_BASE/ORACLESIDinst/rapidinst.all.log
Verify Configuration File				Check \$APPL_BASE/ORACLESIDinst/ORACLE SIDconfig.txt
Change Permissions on Rapidinstall Sub-Directory				chmod 700 \$APPL_BASE/ORACLESIDinst/rapidinst.all
Modify Concurrent Manager Control Script				\$COMN_TOP/admin/scripts/adcmctl.sh - Change startmgr to add sleep=30 (\$FND_TOP/bin/startmgr sysmgr="\$sunpw@\$SDB_NAME" mgrname=\$SDB_NAME sleep=30), CONCSUB to WAIT=Y and ABORT (\$FND_TOP/bin/CONCSUB "\$1" SYSADMIN 'System Administrator' SYSADMIN WAIT=Y CONCURRENT FND ABORT)
Shutdown Application Processes Except Database and Database Listener				\$SCRIPTS_TOP/stop_ORACLESID_apps.ksh
Run adjkey -initialize				\$AD_TOP/bin/adjkey -initialize - Use Defaults ONLY at Prompts
Run adjbuild.sh				\$AD_TOP/bin/adjbuild.sh \$COMN_TOP/util/jinitiator \$COMN_TOP/util/jinitiator/jinit118???.exe {check metalink certify for latest version}
Create Convert Logs				mkdir

Confidential

Page 1 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



Sub-Directory for Archival Purposes				\$APPL_TOP/admin/ORACLESID/log/convert_logs
Create Patch Logs Sub-Directory for Archival Purposes				mkdir \$APPL_TOP/admin/ORACLESID/log/patch_logs
Delete Files from Log/Out/Restart Directories				rm \$APPL_TOP/admin/ORACLESID/log/*, rm \$APPL_TOP/admin/ORACLESID/restart/* and rm \$APPL_TOP/admin/ORACLESID/out/*
Copy Environment File \$APPL_TOP/ORACLESID.env				cp \$APPL_TOP/ORACLESID.env to \$APPL_TOP/ORACLESID.env.install
Validate \$APPLFULL and \$APPLSHAR Variables				Compare \$APPL_TOP/ORACLESID.env With Output From \$AD_TOP/sql/adutconf.sql for Full and Shared Products – Edit ORACLESID.env as Appropriate
Delete Generated Backup Files for AD and FND Product Modules				rm \$AD_TOP/bin/*.sav and rm \$FND_TOP/bin (*.sav)
Backup \$AD_TOP/bin Directory				cp -irp \$AD_TOP/bin to \$AD_TOP/bin_install
Backup \$FND_TOP/bin Directory				cp -irp \$FND_TOP/bin to \$FND_TOP/bin_install
Relink Application DBA (ad) Product Programs Manually				\$AD_TOP/bin/adrelink.sh force=y "ad all"
Validate APPS Schema				Run adadmin Option # 1 (Maintain Application Database Objects) – Then Option # 1 (Validate APPS Schema)
Compile APPS Schema				Run adadmin – Option #1 (Maintain Application Database Objects) – Then Option # 2 (Compile APPS Schema)
Check Invalid Objects from SQL*Plus				SQL*Plus> select count(*) from dba_objects where status = 'INVALID' - (should not exceed 7 Per Oracle Applications Release 11i Release Notes

Confidential

Page 2 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



			Part No. A90345-01)
Compile Menu Information			Run adadmin - Option #1 (Maintain Application Database Objects) - Then Option # 3 (Compile Menu Information - Force = Y) - DO NOT RUN UNLESS PATCH 1788980 APPLIED - See Oracle Applications Release 11i Notes Part No. A90345-01
Recreate Grants and Synonyms			Run adadmin - Option #1 (Maintain Application Database Objects) - Then Option # 3 (Recreate Grants and Synonyms for APPS Schemas) - ERROR - HZ_PARTY_RELATIONSHIPS - Ignore per Metalink Note 154909.1
Compile Flexfields			Run adadmin - Option #1 (Maintain Application Database Objects) - Then Option # 4 (Compile Flexfield Data in AOL Tables)
Relink All Product Modules			Run adadmin - Option #2 (Maintain Application Files) - Then Option # 2 (Relink Applications Programs) - Take Defaults
Generate Message Files			Run adadmin - Option #2 (Maintain Application Files) - Then Option # 5 (Generate Message Files)
Generate Form Files			Run adadmin - Option #2 (Maintain Application Files) - Then Option # 6 (Generate Form Files) - Take Defaults
Generate Report Files			Run adadmin - Option #2 (Maintain Application Files) - Then Option # 7 (Generate Report Files) - Use Defaults
Generate Product Jar Files			Run adadmin - Option #2 (Maintain Application Files) - Then Option # 9 (Generate Product Jar Files) - Use Defaults EXCEPT Force Regeneration = Y
Delete Log/Out/Restart Files if No Errors			rm \$APPL_TOP/admin/ORACLESID/log/*, out/* and restart/* and

Confidential

Page 3 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



				\$APPL_TOP/admin/log/*, out/* and restart/*
Shutdown Database and Database Listener				SSCRIPTS_TOP/stop_ORACLESID_noap ps.ksh
Startup All Application Processes				SSCRIPTS_TOP/start_ORACLESID.ksh
Run Gather Statistics				System Administrator Responsibility - Gather Schema Statistics - ALL
Shutdown All Application Processes				SSCRIPTS_TOP/stop_ORACLESID.ksh
Delete root.sh* Files				In 8.1.7 \$ORACLE_HOME - rm root.sh*
Delete root.sh* Files				In iAS \$ORACLE_HOME (8.1.6) - rm root.sh*
Delete blah* Files				11.5.3 ONLY - In 8.0.X \$ORACLE_HOME - rm blah*
Delete Generated Backup Files for AD and FND Product Modules				rm \$AD_TOP/bin/*.sav and rm \$FND_TOP/bin (*.sav)
Change Temporary Directory Permissions				chmod 777 \$APPL_BASE/ORACLESIDtmp
Full Baseline Backup to Disk of \$APPL_BASE Directories				tar -cvf ORACLESID_baseline_tar \$APPL_BASE
Compress Backup TAR File				compress -vf ORACLESID_baseline_tar
Delete all Unnecessary Database Parameter Files				In 8.1.X \$ORACLE_HOME/dbs - Remove all Files Except initORACLESID.ora and ifilecbo.ora Files
Modify 8.1.7 initORACLESID.ora				In 8.1.7 \$ORACLE_HOME/dbs/initORACLESID.ora - audit_file_dest=\$APPL_BASE/ORACLESIDadm/adump background_dump_dest=\$APPL_BASE/ORACLESIDadm/bdump core_dump_dest=\$APPL_BASE/ORACLESIDadm/cdump user_dump_dest=\$APPL_BASE/ORACLE

Confidential

Page 4 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001



				SIDadm/udump utl_file_dir=\$APPL_BASE/ORACLESIDtmp ifile=\$APPL_BASE/ORACLESIDadm/pfile/ifilecbo.ora
Copy Database Parameter Files				In 8.1.7 \$ORACLE_HOME - cp \$ORACLE_HOME/dbs/*.ora to \$ORACLE_BASE/ORACLESIDadm/pfile
Delete Database Parameter Files				In 8.1.7 \$ORACLE_HOME/dbs - rm *.ora
Create a Soft Link to Database Parameter File From 8.1.7 \$ORACLE_HOME/dbs				In -s \$ORACLE_BASE/ORACLESIDadm/pfile/initORACLESID.ora to \$ORACLE_HOME/dbs/initORACLESID.ora
Modify \$APPL_TOP/ORACLESID.env File				\$APPL_TOP/ORACLESID.env - FORMS60_TIMEOUT=5 APPLPTMP=\$APPL_BASE/ORACLESIDtmp REPORT60TMP=\$APPL_BASE/ORACLESIDtmp APPLCSF=\$APPL_BASE APPLLOG=ORACLESIDlog APPLOUT=ORACLESIDout
Delete APPLSYS.env*				rm \$APPL_TOP/APPLSYS.env*
Delete \$APPL_TOP/*.tmp				rm \$APPL_TOP/*.tmp
Delete DB.env*				In 8.1.7 \$ORACLE_HOME - rm DB.env*
Delete DB.env*				In 8.0.6 \$ORACLE_HOME - rm DB.env*
Delete DB.env*				In iAS \$ORACLE_HOME (8.1.6) - rm DB.env*

Client Name



Backup applprod.txt				cp \$APPL_TOP/admin/applprod to \$APPL_TOP/admin/applprod.install
Backup adconfig.txt				cp \$APPL_TOP /admin/adconfig.txt to \$APPL_TOP /admin/adconfig.install
Backup topfile.txt				cp \$APPL_TOP/admin/topfile.txt to \$APPL_TOP/admin/topfile.install
Startup Database and Database Listener				SSCRIPTS_TOP/start_ORACLESID_noa pps.ksh
Copy Pre-License Manager Application Environment File \$APPL_TOP/ORACLESID.env				cp \$APPL_TOP/ORACLESID.env to \$APPL_TOP/ORACLESID.env.prelimcgr
Run License Manager for Additional Product Modules and Validation				\$AD_TOP/bin/adlicmgr.sh - set DISPLAY Variable First - Validate With APPLFULL/APPLSHAR Variables
Run AD Configuration Utility				\$AD_TOP/sql/adutconf.sql - Generates Listing File - Move Listing File to \$APPL_BASE/ORACLESIDinst Directory
Update Application Environment File ORACLESID.env for New Products (\$APPLFULL and \$APPLSHAR)				Run adadmin - Option #2 (Maintain Application Files) - Then Option # 1 (Create Applications Environment File) - File Updated for Installed Product Modules - Add FORMS60_TIMEOUT=5 export FORMS60_TIMEOUT to File (ORACLESID.env) After Adadmin Completes
Manually Update Application Environment File \$APPL_TOP/ORACLESID.env				Add Missing Product Short Names per adutconf listing to \$APPLSHAR Variable in \$APPL_TOP/ORACLESID.env
Change Permission on Application Administration Directory				chmod 755 \$APPL_TOP /admin
Change Permissions on log, out and restart Directories				chmod 700 \$APPL_TOP/admin/log, out and restart Directories
Change Permissions on				chmod 700

Confidential

Page 6 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



log, out and restart Directories				\$APPL_TOP/admin/ORACLESID/log, out and restart Directories
Change .txt Extension to .log in adalnctl.sh (LOGFILE) and Location to \$APPL_BASE/ORACLESIDlog				\$COMN_TOP/admin/scripts - adalnctl.sh - LOGFILE="\$APPL_BASE/ORACLESIDlog /adalnctl.log"
Change .txt Extension to .log in adfmcctl.sh (FRMLOG) and Location to \$APPL_BASE/ORACLESIDlog				\$COMN_TOP/admin/scripts - adfmcctl.sh - FRMLOG="\$APPL_BASE/ORACLESIDlog /d2lc60.log"
Change .txt Extension to .log in adfmsctl.sh (FRMLOG) and Location to \$APPL_BASE/ORACLESIDlog				\$COMN_TOP/admin/scripts - adfmsctl.sh - FRMLOG="\$APPL_BASE/ORACLESIDlog /d2ls60.log"
Change .txt Extension to .log in adfrmctl.sh (FRMLOG) and Location to \$APPL_BASE/ORACLESIDlog				\$COMN_TOP/admin/scripts - adfrmctl.sh - FRMLOG="\$APPL_BASE/ORACLESIDlog /f60svrm.log"
Modify adfrmctl.sh for Continuous Logging				\$COMN_TOP/admin/scripts - adfrmctl.sh - Change /dev/null to \$FRMLOG
Change .txt Extension to .log in adrepctl.sh (REPSRV_LOG) and Location to \$APPL_BASE/ORACLESIDlog				\$COMN_TOP/admin/scripts - adrepctl.sh - REPSRV_LOG="\$APPL_BASE/ORACLESIDlog /adrepctl.log"
Change .txt Extension to .log in adtcfctl.sh (TCFLOG) and Location to				\$COMN_TOP/admin/scripts - adtcfctl.sh - TCFLOG="\$APPL_BASE/ORACLESIDlog /adtcfctl.log"

Confidential

Page 7 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



\$APPL_BASE/ORACLESI Dlog				
Change .txt Extension to .log in addlnctl.sh (LOGFILE) and Location to \$APPL_BASE/ORACLESI Dlog				\$ORACLE_HOME/appsutil/scripts - addlnctl.sh - LOGFILE="\$APPL_BASE/ORACLESIDlog /addlnctl.log"
Change Apache Logging Parameters				\$APACHE_TOP/Apache/conf/httpds.con f - Change error_log to Apache_error_log and access_log to Apache_access_log - Location to \$APPL_BASE/ORACLESIDlog - CustomLog="\$APPL_BASE/ORACLESIDI og/Apache_access_log common" ErrorLog="\$APPL_BASE/ORACLESIDlog /Apache_error_log" TransferLog="\$APPL_BASE/ORACLESID log/Apache_access_log"
Delete Old Apache Logs				rm \$APACHE_TOP/Apache/logs/*
Shutdown All Processes				\$\$SCRIPTS_TOP/stop_ORACLESID_noap ps.ksh
Start All Database and Application Processes				\$\$SCRIPTS_TOP/start_ORACLESID.ksh
Verify Logs				\$APPL_BASE/ORACLESIDlog
Change Database User sys Password				Per Security Guideline Standards
Change Database User system Password				Per Security Guideline Standards
Lower Security on IE Browser				Internet Options - Security - Enable ActiveX and Security Low
Download JInitiator 1.1.8.?? to Desktop {check metalink certify for latest version}				URL - machinename.domainname:forms port/OA_HTML/US/ICXINDEX.htm - Take Defaults for Desktop Installation
Verify and Exit Applications				Login With Userid/Password - Pick Responsibility - Exit
Shutdown All Processes Except Database and				\$\$SCRIPTS_TOP/stop_ORACLESID_apps. ksh

Confidential

Page 8 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



Listener				
Create Customization Directories				mkdir \$APPL_TOP/customname
Change Permissions to 777 on ORACLESIDappl/custom name Directories				chmod 777 \$APPL_TOP/customname
Create Conversion Data Directory				mkdir \$APPL_BASE/ORACLESIDconv
Change Permissions to 777 on ORACLESIDconv				chmod 777 \$APPL_BASE/ORACLESIDconv
Create Interface Data Directory				mkdir \$APPL_BASE/ORACLESIDintf
Change Permissions to 777 on ORACLESIDintf				chmod 777 \$APPL_BASE/ORACLESIDintf
Create custom.env File				\$APPL_TOP/ORACLESIDcustom.env
Add ORACLESIDcustom.env Reference to ORACLESID.env File				\$APPL_TOP/ORACLESID.env
Create Patchset Compare Directory				\$PATCH_TOP/patchset_compare_tool
Download Latest Patchset Comparison Script From Oracle FTP Site.				ftp://oracle-ftp.oracle.com/apps/patchsets.sh to \$PATCH_TOP/patchset_compare_tool/p atchsets.sh
Run Patchset Comparison Script Against \$APPL_TOP/admin/ORACLESID/applptch.txt				\$PATCH_TOP/patchset_compare_tool/p atchsets.sh
Review and Compare the Patchset Report and Download Missing Patches				\$PATCH_TOP/patchset_compare_tool/ /Report_11i.txt
Shutdown All Processes				\$SCRIPTS_TOP/stop_ORACLESID_noap ps.ksh
Backup appsweb.cfg Files				Copy \$FND_TOP/resource/appsweb.cfg

Confidential

Page 9 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001



				to appsweb.cfg.install. Copy \$OA_HTML/bin/resource/appsweb.cfg to appsweb.cfg.install.
Verify \$FND_TOP/resource/appsweb.cfg and Copy to \$OA_HTML/bin.				Edit For: serverPort= serverName= domainName= Jinitiator Information - Version and Class
Increase Security on IE Browser				Internet Options - Change to Medium Security
Start All Application Processes				\$\$SCRIPTS_TOP/start_ORACLESID.ksh
Change Site Name Profile				System Administrator Responsibility - ORACLESID
Change Applet Plug-In Type				Version 1.1.8.7
Change Guest Password				Change to Oracle to Match \$FND_TOP/secure/ursa*.dbc Files - Should be ORACLE
Set Workflow Administrator Preference and Turn Off Workflow Notifications				As SYSADMIN User and System Administrator Responsibility - Workflow Global Preferences - Change No Email Notification, Jinitiator Version and Class
Change sysadmin Password				Change SYSADMIN Password from Default to Match Security Guideline Standards
Shutdown All Processes Except Database and Listener				\$\$SCRIPTS_TOP/stop_ORACLESID_noaps.ksh
Apply Latest AD Patch				\$PATCH_TOP
Apply Latest Family Patches				\$PATCH_TOP
Run Patchset Comparison Script Against \$APPL_TOP/admin/ORA				\$PATCH_TOP/patchset_compare_tool/patchsets.sh

Client Name



CLESID/aplptch.txt				
Apply Latest Product Module Patches Still Missing for Fully Installed Products				\$PATCH_TOP
Run Patchset Comparison Script Against \$APPL_TOP/admin/ORA CLESID/aplptch.txt				\$PATCH_TOP/patchset_compare_tool/patchsets.sh
Apply Latest Product Module Patches Still Missing for Shared Installed Products				\$PATCH_TOP
Run Patchset Comparison Script Against \$APPL_TOP/admin/ORA CLESID/aplptch.txt				\$PATCH_TOP/patchset_compare_tool/patchsets.sh
Review and Compare the Patchset Report and Download Missing Patches				\$PATCH_TOP/patchset_compare_tool/Report_11i.txt
Apply Any New Patches				\$PATCH_TOP
Generate Current Patchset html Page				\$PATCH_TOP/patchset_compare_tool/patchsets.sh aplptch=\$APPL_BASE/ORACLESIDapl/admin/ORACLESID/aplptch.txt htmlout=Report_11i.html silent=y And Copy Report_11i.txt into Report_11i.html After Modifications for html Applied.
Create Symbolic Link for Report_11i.html Page				ln -s \$PATCH_TOP/patchset_compare_tool/Report_11i.html \$COMN_TOP/portal/Report_11i.html
Backup Portal Page				cp \$COMN_TOP/portal/applist.html to applist.install
Modify Portal Page				Modify \$COMN_TOP/portal/applist.html

Confidential

Page 11 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



				for Report_11i.html html File
Delete Generated Backup Files for AD and FND Product Modules				rm \$AD_TOP/bin/*.sav and rm \$FND_TOP/bin (*.sav)
Backup \$AD_TOP/bin Directory				cp \$AD_TOP/bin to \$AD_TOP/bin_patch
Backup \$FND_TOP/bin Directory				cp \$FND_TOP/bin to \$FND_TOP/bin_patch
Relink Application DBA (ad) Product Programs Manually				\$AD_TOP/bin/adrelink.sh force=y "ad all"
Validate APPS Schema				Run adadmin Option # 1 (Maintain Application Database Objects) - Then Option # 1 (Validate APPS Schema)
Compile APPS Schema				Run adadmin - Option #1 (Maintain Application Database Objects) - Then Option # 2 (Compile APPS Schema)
Check Invalid Objects from SQL*Plus				SQL*Plus> select count(*) from dba_objects where status = 'INVALID' - (Should not Exceed 12) - 4 Package Bodies Need To Be Compiled Manually (SQL*Plus> alter package OWNER.OBJECT_NAME compile body;) 44 Invalid Objects
Compile Menu Information				Run adadmin - Option #1 (Maintain Application Database Objects) - Then Option # 3 (Compile Menu Information - Force = Y) - DO NOT RUN UNLESS PATCH 1788980 APPLIED - See Oracle Applications Release 11i Notes Part No. A90345-01
Recreate Grants and Synonyms				Run adadmin - Option #1 (Maintain Application Database Objects) - Then Option # 3 (Recreate Grants and Synonyms for APPS Schemas) - ERROR - HZ_PARTY_RELATIONSHIPS - Ignore per Metalink Note 154909.1
Compile Flexfields				Run adadmin - Option #1 (Maintain Application Database Objects) - Then

Confidential

Page 12 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



				Option # 4 (Compile Flexfield Data in AOL Tables)
Relink All Product Modules				Run adadmin - Option #2 (Maintain Application Files) - Then Option # 2 (Relink Applications Programs) - Take Defaults
Generate Message Files				Run adadmin - Option #2 (Maintain Application Files) - Then Option # 5 (Generate Message Files)
Generate Form Files				Run adadmin - Option #2 (Maintain Application Files) - Then Option # 6 (Generate Form Files) - Take Defaults
Generate Report Files				Run adadmin - Option #2 (Maintain Application Files) - Then Option # 7 (Generate Report Files) - Use Defaults
Generate Product Jar Files				Run adadmin - Option #2 (Maintain Application Files) - Then Option # 9 (Generate Product Jar Files) - Use Defaults EXCEPT Force Regeneration = Y
Start Application Processes				\$\$SCRIPTS_TOP/start_ORACLESID_apps .ksh
Run Gather Statistics				System Administrator Responsibility - Gather Schema Statistics - ALL
Delete Generated Backup Files for AD and FND Product Modules				rm \$AD_TOP/bin/*.sav and rm \$FND_TOP/bin (*.sav)
Download Cloning Patches From Metalink				\$PATCH_TOP - ad_1643475 and ad_1636653
Apply ad_1643475				\$PATCH_TOP - AD One-Off Patch to Fix File Errors - Apply C Driver
Apply ad_1906056				\$PATCH_TOP - AD One-Off Patch for Cloning - Apply C Driver
Download Password Utility Patch From Metalink				\$PATCH_TOP - fnd_1685689
Apply fnd_1685689				\$PATCH_TOP- FND One-Off Patch for Password Changing - Apply C and D Drivers

Confidential

Page 13 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



Download Security Patch From Metalink				\$PATCH_TOP - fnd_1779336
Apply fnd_1779336				\$PATCH_TOP - FND One-Off Patch for ADI and Web Security - Apply C, D and G Drivers
Copy aps7 Software				\$\$SCRIPTS_TOP/../../aps7
Run apsprep.sql				\$APPL_BASE/ORACLESIDscr/aps7/sql - Sets Up Database for APS Software
Run alter_extents.sql				\$APPL_BASE/ORACLESIDscr/aps7/sql - Alters Application Table and Index Maximum Extents to Consistent 500
Reconfigure Redo Logs				\$APPL_BASE/ORACLESIDscr/sql/creat e_redo.sql - Configure 10 Redo Logs - Each 100MB
Reconfigure Rollback Segments				\$APPL_BASE/ORACLESIDscr/sql/creat e_rollbacks.sql - Configure 20 Rollback Segments - Each 20M, Configure 1 Large Rollback Segment - 500M
Alter sys and system users temporary tablespace to temp				Alter user sys temporary tablespace TEMP; Alter user system temporary tablespace TEMP.
Modify Locally Managed Tablespaces				\$APPL_BASE/ORACLESIDscr/sql/modif y_lmt.sql - All EXCEPT system and rbs Tablespaces
Modify Temp Tablespace Settings				\$APPL_BASE/ORACLESIDscr/sql/modif y_temp.sql
Run AD Configuration Utility				\$AD_TOP/sql/adutconf.sql - Generates Listing File for Verification
Run APS Scripts for Report				\$\$SCRIPTS_TOP/../../aps7/sql/tf, rbs and filemap.sql - Verify
Delete Log/Out/Restart Files After Resolving Errors				rm \$APPL_TOP/admin/ORACLESID/log/*, out/* and restart/* and \$APPL_TOP/admin/log/*, out/* and restart/*
Move Patch Logs				mv \$APPL_TOP/admin/ORACLESID/log/ad patch* to \$APPL_TOP/admin/ORACLESID/patch_

Confidential

Page 14 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



				logs
Shutdown Database and Database Listener				\$\$SCRIPTS_TOP/stop_ORACLESID_noap ps.ksh
Full Export of Database to Disk				\$\$SCRIPTS_TOP/export_ORACLESID.ksh h - Export and Log File Location is \$APPL_BASE/ORACLESIDexp
Full Baseline Backup to Tape				\$\$SCRIPTS_TOP/backup_to_tape.ksh
Full Baseline Backup to Disk (\$APPL_BASE) of \$APPL_BASE Directories				tar -cvf ORACLESID_baseline_premultiorg_tar \$APPL_BASE
Compress Backup TAR File				compress -vf ORACLESID_baseline_premultiorg_tar
Rename Previous Patchset Compare Tool Directory				mv \$PATCH_TOP/patchset_compare_tool to \$PATCH_TOP/patchset_compare_tool_0 62701_ok
Create Patchset Compare Directory				\$PATCH_TOP/patchset_compare_tool
Download Latest Patchset Comparison Script From Oracle FTP Site.				ftp://oracle-ftp.oracle.com/apps/patchsets.sh to \$PATCH_TOP/patchset_compare_tool/p atchsets.sh
Run Patchset Comparison Script Against \$APPL_TOP/admin/ORACLESID/applptch.txt				\$PATCH_TOP/patchset_compare_tool/p atchsets.sh
Review and Compare the Patchset Report and Download Missing Patches				\$PATCH_TOP/patchset_compare_tool/R eport_11i.txt
Generate Current Patchset html Page				\$PATCH_TOP/patchset_compare_tool/p atchsets.sh applptch=\$APPL_BASE/ORACLESIDapp l/admin/ORACLESID/applptch.txt htmlout=Report_11i.html silent=y And Copy Report_11i.txt into Report_11i.html After Modifications for html Applied.

Confidential

Page 15 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



Verify Symbolic Link for Report_11i.html Page				In -s \$PATCH_TOP/patchset_compare_tool/Report_11i.html \$COMN_TOP/portal/Report_11i.html
Backup Portal Page				cp \$COMN_TOP/portal/applist.html to applist.install
Modify Portal Page				Modify \$COMN_TOP/portal/applist.html for Report_11i.html html File
Convert to Multi-Org				After Functional Setups - Run adadmin - Option #1 (Maintain Application Database Objects) - Then Option # 7 (Convert to Multi-Org) - Take Defaults
Move Multi-Org Patch Log				mv \$APPL_TOP/admin/ORACLESID/log/ad patch* to \$APPL_TOP/admin/ORACLESID/conve rt_logs
Shutdown Database and Database Listener				\$\$SCRIPTS_TOP/stop_ORACLESID_noap ps.ksh
Full Export of Database to Disk				\$\$SCRIPTS_TOP/export_ORACLESID.ksh - Export and Log File Location is \$APPL_BASE/ORACLESIDexp
Full Baseline Backup to Tape				\$\$SCRIPTS_TOP/backup_to_tape.ksh
Full Baseline Backup to Disk (\$APPL_BASE) of \$APPL_BASE Directories				tar -cvf ORACLESID_baseline_postmultiorg_tar \$APPL_BASE
Compress Backup TAR File				compress -vf ORACLESID_baseline_postmultiorg_tar
Update the Patch Matrix Status Report for Applied Patches				File on Network Drive
Update the Port Grid for All Ports Used				File on Network Drive
Email Status to Team				
Install ADI on Desktops				Download Latest ADI from Metalink
Apply ADI Patches				\$PATCH_TOP

Confidential

Page 16 of 17

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001

Client Name



Run Active Users Report				System Administrator Responsibility
Run Responsibilities Report				System Administrator Responsibility
Run Profiles Report				System Administrator Responsibility
Modify Concurrent Manager Definitions and Work Shifts				System Administrator Responsibility

Confidential

©Copyright 2001 Solution Beacon, LLC All Rights Reserved.

Client Software Version:

Client Platform/OS:

Revision Date: September 19, 2001